

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
REQUEST FOR FILING APPLICATION UNDER 37 CFR 53(b)  
WITHOUT FILING FEE OR EXECUTED INVENTOR'S DECLARATION

Assistant Commissioner for Patents  
Washington, D.C. 20231

Atty. Dkt. 3572-7  
Date: **September 23, 1999**

jc678 U.S. PTO  
09/401730  
09/23/99

Sir:

This is a request for filing a new PATENT APPLICATION under Rule 53(b) entitled:

**DEVICE FOR SECURING AT LEAST ONE OPTICAL FIBRE TO AN OPTICAL APPARATUS**

with a filing fee and/or without an executed inventor's oath/declaration.

This application is made by the below identified inventor(s). Attached hereto are the following papers:

☐ An abstract together with

☐ pages of specification and claims including

☐ numbered claims and also attached is/are

☐ sheets of accompanying drawings.

This application is based on the following prior foreign application(s):

**Application No.**

**Country**

**Filing Date**

**98830558.7**

**EP**

**23 September 1998**

respectively, the entire content of which is hereby incorporated by reference in this application, and priority is hereby claimed therefrom.

☐ This application is based on the following prior provisional application(s):

**Application No.**

**Filing Date**

respectively, the entire content of which is hereby incorporated by reference in this application, and priority is hereby claimed therefrom.

☐ Certified copy/ies of foreign applications attached.

This application is a ☐ continuation/☐ division/☐ continuation-in-part of application Serial No. , filed

Please amend the specification by inserting before the first line: --This application is a ☐ continuation/☐ division/☐ continuation-in-part of application Serial No. , filed , the entire content of which is hereby incorporated by

reference in this application.--

Please amend the specification by inserting before the first line: --This is a continuation of PCT application No.

, filed , the entire content of which is hereby incorporated by reference in this application.--

Please amend the specification by inserting before the first line: --This application claims the benefit of U.S.

Provisional Application No. , filed , the entire content of which is hereby incorporated by reference in this application.--

☒ Preliminary amendment to claims (attached hereto), to be entered before calculation of the fee.

Also attached. Information Disclosure Statement

Inventor:

**Enzo**

(first)

MI

**FEI**

(last)

**Italian**

(citizenship)

Residence: (city)

**Bologna**

(state/country)

**Italy**

Post Office Address:

**Via Budrie 2A, San Giovanni in Persiceto, Bologna, Italy**

(incl zip code)

**I-40017**

2.

Inventor:

**Daniele**

(first)

MI

**LIPPI**

(last)

**Italian**

(citizenship)

Residence: (city)

**Bologna**

(state/country)

**Italy**

Post Office Address:

**Via Brodolini 8, Bologna, Italy**

(incl zip code)

**I-40133**

NOTE: FOR ADDITIONAL INVENTORS, check box ☐ and attach sheet with same information.

Address all future communications to NIXON & VANDERHYE P.C., 1100 North Glebe Road, 8<sup>th</sup> Floor, Arlington, Virginia 22201.

1100 N. Glebe Road, 8th Floor

Arlington, Virginia 22201

Telephone: (703) 816-4000

Facsimile: (703) 816-4100

**NIXON & VANDERHYE P.C.**

By Atty.: **Stanley C. Spooner**, Reg. No. 27,393

Signature: \_\_\_\_\_

SCS:kmm

Our Ref.: 3572-7  
GC/me/DAL035BUS

# ***U.S. PATENT APPLICATION***

***Inventor(s):*** Enzo FEI and Daniele LIPPI

***Invention:*** Device for Securing at Least One Optical Fibre to an Optical Apparatus

***NIXON & VANDERHYE P.C.  
ATTORNEYS AT LAW  
1100 NORTH GLEBE ROAD  
8<sup>TH</sup> FLOOR  
ARLINGTON, VIRGINIA 22201-4714  
(703) 816-4000  
Facsimile (703) 816-4100***

## ***SPECIFICATION***

"Device for securing at least one optical fibre to an optical apparatus"

\* \* \* \* \*

The present invention relates to a device for securing at least one optical fibre to an optical apparatus.

5        There are known optical apparatus such as, for example, optical sensors operating with a single emission wavelength (colour), comprising a photo-emitter and a photo-detector (photo-elements). The photo-emitter generates a beam of light which is channelled into an optical fibre so that it is transported into a region to be monitored. The  
10       light reflected from the monitored region is channelled into another optical fibre and transported to the photo-detector.

      In known optical sensors, each of the two optical fibres, that used for emission and that used for detection, is held in position, with respect to the photo-emitter and the photo-detector, by its own securing means of  
15       the screw, lever or button type.

      Consequently, each securing means requires its own stage of manufacture, and each fibre requires its own alignment and fixing operation.

20       However, these known sensors do not enable the operator to check in a direct way the correct alignment of a fibre with a photo-element.

      A first aspect of the present invention therefore consists of a device for securing at least one optical fibre to an optical apparatus, the said optical apparatus comprising at least one photo-element mounted on a supporting element and at least one optical fibre which can be  
25       connected to the said photo-element by means of the said securing device, characterized in that at least a part of the said securing device is made from a transparent material which makes a region of the coupling between the fibre and the photo-element visible.

According to a preferred embodiment, the said device comprises a cover made from transparent material. The said supporting element is also made from transparent material.

5 Preferably, the said transparent material is selected from the group comprising glass, polycarbonate (PC), polymethyl methacrylate (PMMA), polystyrene (PS), acrylonitrile-styrene (SAN), acrylonitrile-butadiene-styrene (ABS), polyphenylene oxide (PPO), polyurethane (PUR), polysulphone (PSU), polyamide (PA), polyvinyl chloride (PVC), and polyphenylene sulphide (PPS).

10 The known securing means are also particularly inadequate for multiple-fibre optical sensors comprising two or three photo-emitters, each capable of emitting a light beam of a predetermined colour and optically connected to a corresponding emission fibre. Typically, for  
15 example, three-fibre optical sensors may have red emission for the detection of white-green contrasts, and blue emission for the detection of white-yellow contrasts. Four-fibre sensors offer the function of colour reading and discrimination by means of blue, green and red emission. These optical sensors make different types of emission available to a user and, therefore, have the advantage of being adaptable to different  
20 applications.

A second aspect of the present invention therefore consists of a device for securing at least one optical fibre to an optical apparatus, the said optical apparatus comprising at least one photo-element, at least one optical fibre which can be connected to the said photo-element,  
25 and at least one supporting element provided with at least one guide hole for the said at least one optical fibre, characterized in that it comprises a slide provided with at least one slot, the said slide assuming a first and a second predetermined position, the said slot, in the said first position of the said slide, being coaxial with the said hole  
30 of the said supporting element and freely housing the said optical fibre,

and the said slot, in the said second position of the said slide, being out of alignment with the said hole and exerting on the said optical fibre a force which keeps the optical fibre secured in the said hole.

5 According to a preferred embodiment, the said slide is provided with at least two slots. In particular, the said optical apparatus is provided with at least two optical fibres.

10 According to another preferred embodiment, the device comprises a cover provided with at least one hole for the passage of the said optical fibre, the said cover being provided with an enclosure capable of supporting the said slide so that it is free to slide, and of housing elastic means in engagement with the said slide to keep it in the said second position.

15 Preferably, the said slot comprises a semi-circular portion having a radius greater than that of the said optical fibre.

In particular, the said semi-circular portion of the said slot has a projecting arm.

The said slot is substantially C-shaped.

20 Additionally, the said semi-circular portion has a notch capable of imparting elasticity to the said arm.

According to a further preferred embodiment, the said slide is provided with a pin which is used for centring the said elastic means.

The said slide is advantageously made from transparent material. The said cover is also made from transparent material. The said supporting element is also made from transparent material.

25 Preferably, the said transparent material is selected from those mentioned previously.

In this way a simple and efficient device for securing one or more optical fibres to an optical apparatus is made.

30 Making the slide and the cover from transparent material provides many advantages.

It is possible to see the optical fibres and the holes of the supporting element through the cover and the slide during the assembly operations. This makes it possible to check the correctness of the coupling of a fibre to a predetermined photo-element (photo-emitter or photo-detector) and the positioning of each fibre with respect to its particular photo-element, which is known to be a very delicate operation. It is also possible to check, at the moment of insertion of the optical fibres into the holes of the supporting element, whether the holes are free or obstructed, and whether a fibre is damaged, by the tearing of a sheath for example.

Finally, the photo-elements are visible through a very wide angle. This enables the different photo-emitters to be clearly distinguished by the colours of the light beams emitted and also enables the photo-emitters to be distinguished with certainty from the photo-detectors. Moreover, it is possible to check, even from a distance, whether any of them are damaged.

The securing device according to the invention is very practical in terms of assembly, since the slide, by means of each slot, performs the double function of releasing and securing an optical fibre. This is achieved by simple movements of the slide between two predetermined positions. Moreover, a multiplicity of optical fibres of the optical apparatus can be released and secured simultaneously by operating the slide alone.

The degree of force, or compression, exerted by each slot on each optical fibre, is predetermined, to make it possible to fix the fibre without damaging it or adversely affecting its capacity for transmitting light.

Characteristics and advantages of the invention will now be explained with reference to an embodiment illustrated by way of non-restrictive example in the attached figures, of which:

Fig. 1 is an exploded view of a device for securing optical fibres to an optical apparatus, made according to the invention;

Fig. 2 is a front view of a slide of the securing device shown in Fig. 1;

Fig. 3 is a rear view of a cover of the securing device shown in Fig.

5 1;

Fig. 4 is a perspective view of the optical apparatus provided with the securing device shown in Fig. 1;

Fig. 5 is a front view of a variant of the slide shown in Figs. 1 and 2.

10 Figs. 1 and 4 show a device 1 for securing four optical fibres 2, 3, 4 and 5 to an optical apparatus 6 consisting, in this particular case, of an optical sensor.

The device 1 comprises a slide 7 provided with four slots 8 disposed in series. Each slot 8 has a semi-circular portion 9 having a radius greater than that of an optical fibre, and provided with a projecting arm  
15 10. Each slot is substantially C-shaped. The semi-circular portion 9 has a notch 30 (Fig. 2) which has the function of imparting a certain degree of elasticity to the arm 10. The slide is provided with an operating button 13 and an end pin 11 which is used for centring a spring 12.

The device 1 also comprises a cover 14 provided with an enclosure  
20 15 consisting of a substantially parallelepipedal recess capable of supporting the slide 7 so that it is free to slide, and of housing the spring 12. The cover 14 is provided with four holes 16 for the passage of the optical fibres 2, 3, 4 and 5. The cover 14 is also provided with projections 18, one above, one below and two in intermediate positions  
25 (Fig. 3), which act as end stops for the slide 7. The cover 14 also has four recesses 19 whose function will be explained subsequently.

The slide 7 and the cover 14 are made from transparent material selected from the group comprising glass, polycarbonate (PC), polymethyl methacrylate (PMMA), polystyrene (PS), acrylonitrile-  
30 styrene (SAN), acrylonitrile-butadiene-styrene (ABS), polyphenylene

oxide (PPO), polyurethane (PUR), polysulphone (PSU), polyamide (PA), polyvinyl chloride (PVC), and polyphenylene sulphide (PPS).

5 The optical sensor 6 comprises photo-elements consisting of three photo-emitters 20, 21 and 22 and a photo-detector 23. Each photo-emitter consists, for example, of a light-emitting diode (LED) and emits a light beam of a predetermined colour. For example, the light beams emitted by the three photo-emitters 20, 21 and 22 are blue, green and red respectively, or other colours. The optical sensor 6 also comprises a supporting element 24 for the photo-emitters 20, 21 and 22 and for  
10 the photo-detector 23. The supporting element 24 is provided with four guide holes 25 for the optical fibres 2, 3, 4 and 5. Sealing gaskets 26 for the optical fibres, consisting of O-rings capable of providing protection according to IP67, are fitted in the holes 25. The supporting element 24 is provided with four tabs 27 which are snap-fitted into the  
15 recesses 19 of the cover 14 at the time of assembly of the securing device 1 and of the optical sensor 6. The sensor 6 is provided with a container 28 (Fig. 4) in which the supporting element 24 and the photo-elements 20, 21, 22 and 23 are mounted. In the sensor 6, the photo-emitters 20, 21 and 22 are optically connected to the optical fibres 2, 3 and 4 respectively, while the photo-detector 23 is optically connected to  
20 the optical fibre 5. The optical fibres 2, 3 and 4 transport the light beams towards a region to be monitored, while the optical fibre 5 transports the light reflected (diffused) from the monitored region towards the photo-detector 23.

25 The supporting element 24 may also be made from a material selected from the group indicated above.

According to a variant, the optical apparatus 6 may comprise two photo-emitters and two photo-detectors.



Fig. 5 shows a slide 17 in which parts identical to those of the slide 7 are indicated by the same numbers. In the slide 17, the semi-circular portions 9 of the slots 8 have no notches.

5 The securing device 1 is assembled by mounting the spring 12 on the pin 11 of the slide 7 and inserting the slide and spring in the recess 15 of the cover 14. The spring 12 pushes the slide 7 upwards against the upper end stop projection 18. In this way, the button 13 of the slide emerges from the enclosure 15 of the cover 14 and can be operated manually (Fig. 4).

10 The sensor 6 is assembled by mounting in the container 28 the supporting element 24 pre-assembled with the photo-emitters 20, 21 and 22, the photo-detector 23 and the sealing gaskets 26 disposed in the holes 25. The securing device 1 is then fixed to the sensor 6 by snap-fitting the cover 14 on the supporting element 24, by means of the  
15 tabs 27 which fit into the recesses 19. At this point, the slide 7 is pushed downwards by pressure on the button 13, against the action of the spring 12. In this way, the spring 7 assumes a first end position in which the semi-circular portions 9 of the slots 8 of the slide 7 are disposed coaxially with the holes 16 of the cover 14 and with the holes  
20 25 of the supporting element 24. The optical fibres 2, 3, 4 and 5 can then be inserted through the holes 16, the semi-circular portions 9 of the slots 8 and the holes 25 until they are brought into contact with the photo-emitters 20, 21 and 22 and with the photo-detector 23. Since the cover 14 and the slide 17 are made from transparent material, it is  
25 possible to see the optical fibres and to check whether they enter the holes 25 without obstruction and whether they are positioned correctly with respect to the photo-elements. After this, the button 13 of the slide 7 is released, and the slide is pushed upwards by the spring 12, being stopped by the upper projection 18 of the cover 14. In this way, the  
30 slide 7 assumes a second end position in which the semi-circular

portions 9 of the slots 8 are out of alignment with the holes 16 and 25 and exert a force of a predetermined value on the optical fibres 2, 3, 4 and 5 to secure them in the holes 25.

## CLAIMS

1. Device (1) for securing at least one optical fibre (2; 3; 4; 5) to an optical apparatus (6), the said optical apparatus (6) comprising at least one photo-element (20; 21; 22; 23) mounted on a supporting element (24) and at least one optical fibre (2; 3; 4; 5) which can be connected to the said photo-element (20; 21; 22; 23) by means of the said securing device (1), characterized in that at least a part of the said securing device (1) is made from a transparent material which makes a region of the coupling between the fibre and the photo-element visible.
2. Securing device (1) according to claim 1, characterized in that it comprises a cover (14) made from transparent material.
3. Securing device (1) according to claim 1, characterized in that the said supporting element (24) is made from transparent material.
4. Securing device (1) according to any one of the preceding claims 1 to 3, characterized in that the said transparent material is selected from the group comprising glass, polycarbonate (PC), polymethyl methacrylate (PMMA), polystyrene (PS), acrylonitrile-styrene (SAN), acrylonitrile-butadiene-styrene (ABS), polyphenylene oxide (PPO), polyurethane (PUR), polysulphone (PSU), polyamide (PA), polyvinyl chloride (PVC), and polyphenylene sulphide (PPS).
5. Device (1) for securing at least one optical fibre (2; 3; 4; 5) to an optical apparatus (6), the said optical apparatus (6) comprising at least one photo-element (20; 21; 22; 23), at least one optical fibre (2; 3; 4; 5) which can be connected to the said photo-element (20; 21; 22; 23), and at least one supporting element (24) provided with at least one guide hole (25) for the said at least one optical fibre (2; 3; 4; 5), characterized in that it comprises a slide (7) provided with at least one slot (8), the said slide (7) assuming a first and a second predetermined position, the said slot (8), in the said first position of

- the said slide (7), being coaxial with the said hole (25) of the said supporting element (24) and freely housing the said optical fibre (2; 3; 4; 5), and the said slot (8), in the said second position of the said slide (7), being out of alignment with the said hole (25) and exerting on the said optical fibre (2; 3; 4; 5) a force which keeps the optical fibre (2, 3, 4, 5) secured in the said hole (25).
- 5
6. Securing device (1) according to claim 5, characterized in that the said slide (7) is provided with at least two slots (8).
7. Securing device (1) according to claim 6, characterized in that the
- 10 the said optical apparatus (6) is provided with at least two optical fibres (2, 3, 4, 5).
8. Securing device (1) according to claim 5, characterized in that it comprises a cover (14) provided with at least one hole (15) for the passage of the said optical fibre (2; 3; 4; 5), the said cover (14)
- 15 being provided with an enclosure (15) capable of supporting the said slide (7) so that it is free to slide, and of housing elastic means (12) in engagement with the said slide (7) to keep it in the said second position.
9. Securing device (1) according to claim 5, characterized in that the
- 20 the said slot (8) comprises a semi-circular portion (9) having a radius greater than that of the said optical fibre (2; 3; 4; 5).
10. Securing device (1) according to claim 9, characterized in that the said semi-circular portion (9) of the said slot (8) has a projecting arm (10).
- 25 11. Securing device (1) according to claims 9 and 10, characterized in that the said slot (8) is substantially C-shaped.
12. Securing device (1) according to claim 10, characterized in that the said semi-circular portion (9) has a notch (30) capable of imparting elasticity to the said arm (10).

13. Securing device (1) according to claim 8, characterized in that the said slide (7) is provided with a pin (11) which is used for centring the said elastic means (12).
14. Securing device (1) according to claim 5, characterized in that the said slide (7) is made from transparent material.
15. Securing device (1) according to claim 8, characterized in that the said cover (14) is made from transparent material.
16. Securing device (1) according to claim 5, characterized in that the said supporting element (24) is made from transparent material.
17. Securing device (1) according to any one of the preceding claims 14 to 16, characterized in that the said transparent material is selected from the group comprising glass, polycarbonate (PC), polymethyl methacrylate (PMMA), polystyrene (PS), acrylonitrile-styrene (SAN), acrylonitrile-butadiene-styrene (ABS), polyphenylene oxide (PPO), polyurethane (PUR), polysulphone (PSU), polyamide (PA), polyvinyl chloride (PVC), and polyphenylene sulphide (PPS).

"Device for securing at least one optical fibre to an optical apparatus"

\*\*\*\*\*

# ABSTRACT

5 A device (1) for securing at least one optical fibre (2; 3; 4; 5) to an optical apparatus (6) is proposed, comprising at least one photo-element (20; 21; 22; 23) mounted on a supporting element (24) and at least one optical fibre (2; 3; 4; 5) which can be connected to the photo-element (20; 21; 22; 23); the securing device (1) comprises at least one transparent part, such that a region of the coupling between the fibre  
10 and the photo-element is visible.

A securing device (1) is also proposed, comprising a slide (7) provided with at least one slot (8), which assumes a first and a second position; in the first position, the slot (8) is coaxial with a hole (25) in the supporting element (24) and freely houses the optical fibre (2; 3; 4; 5),  
15 while in the second position the slot (8) is out of alignment with the hole (25) and exerts on the optical fibre (2; 3; 4; 5) a force which keeps it secured in the hole (25). (Fig.1)

